



توتال جلف لإعمال الحداكه والألمنيوم والزجاج ذ.م.م

**Total gulf L.L.C.**

★ Automatic Doors ★ Steel Doors ★ Aluminium & Glass

## **STEEL SLATE FIRE ROLLING SHUTTER** **(SINGLE SKIN)**



تليفون : ٧١١٧٨٢٦-٠٦ , فاكس : ٧١١٧٨٢٧-٠٦ , ص.ب : ٤٨٣٨ , أم القيوين - ا.ع.م

Tel.: 06-7667826, Fax: 06-7667827, P.O. Box: 4838, Umm Al Quwain - U.A.E.

E-mail : [info@totalgulfuae.com](mailto:info@totalgulfuae.com), Website: [www.totalgulfuae.com](http://www.totalgulfuae.com)



توتال جلف لإعمال الحداكة والألمنيوم والزجاج ذ.م.م

**Total gulf L.L.C.**

★ Automatic Doors ★ Steel Doors ★ Aluminium & Glass

## **STEEL SLATE FIRE ROLLING SHUTTER** **(SINGLE SKIN)**

### **SPECIFICATION**

- ❖ Safe, simple, inexpensive and repeatable drop testing is now made possible in any facility with a flip of a handle.
- ❖ No ladders, tools or equipment are required to drop test and reset Simple Test Fire Doors.
- ❖ Drop speed is governed by a quiet, centrifugal brake to between 6" to 24" per second.
- ❖ Gear reduced chain hoist operation is standard, efficient and economical.
- ❖ Manual push-up operation & motor operation is optional.
- ❖ 165 degree fusible links are provided as standard detection/release devices.
- ❖ U.L. Labels are provided from 3/4 hour to 4 hour for labeled and for oversized doors.
- ❖ Guides mount to approved masonry, steel and sheetrock jambs.
- ❖ Upward-expanding guides may be welded to approve steel jambs.
- ❖ Fail-safe time delayed releases, smoke detectors and audible and visual warning systems are optional.
- ❖ Installation time is reduced significantly due to elimination of complicated release assemblies.
- ❖ Slats size available 75mm / 100mm, width max- 9metre.
- ❖ Slats thick 1.0 mm to 2.0 mm available
- ❖ **Available Make – UK, Australia, Malaysia, and UAE.**